

# OPTONICA



## Projecteur LED SMD IP65 Corps Blanc avec Capteur

### Puissance

- 10W

### Couleur de lumiere



Lumière blanche

### Stamps





## Technical Specification

|                                     |                 |
|-------------------------------------|-----------------|
| <b>Reference catalogue</b>          | 15837           |
| <b>Brand</b>                        | Optonica        |
| <b>Product Code</b>                 | FL10-B3         |
| <b>Power</b>                        | 10W             |
| <b>Energy Consumption</b>           | 10 kWh/1000h    |
| <b>Input voltage</b>                | AC180-265V      |
| <b>Flux</b>                         | 900 lm          |
| <b>FLUX per watt</b>                | 90lm/W          |
| <b>IP</b>                           | 65              |
| <b>Dimmable</b>                     | No              |
| <b>Correlated Color Temperature</b> | 6000K           |
| <b>Light Color</b>                  | Lumière blanche |
| <b>EAN Code</b>                     | 3801057158372   |
| <b>Energy Efficiency Label</b>      | F               |

|   |                  |
|---|------------------|
| <b>Beam angle</b>                               | 120°             |
| <b>On/Off Cycles</b>                            | 25 000x          |
| <b>Instant On</b>                               | 0.1s             |
| <b>Material</b>                                 | ALU + Glass      |
| <b>Operating Frequency</b>                      | 50-60 Hz         |
| <b>Temperature</b>                              | -20°C / +40°C    |
| <b>Life span</b>                                | 25 000 Hours     |
| <b>Body Color</b>                               | White            |
| <b>LED Type</b>                                 | SMD              |
| <b>Lumen maintenance at end of service life</b> | 70%              |
| <b>Size of product</b>                          | 105x134.5x26mm   |
| <b>Size of package</b>                          | 11.5x5x14.3cm    |
| <b>Size of Box</b>                              | 59.5x26.5x30x5cm |
| <b>Items per pack</b>                           | 1                |
| <b>Items per box</b>                            | 50               |
| <b>Cable</b>                                    | 15 cm            |
| <b>Detection Distance</b>                       | 8 M              |
| <b>Sensitivity angle</b>                        | 120 degree       |

|                      |                         |
|----------------------|-------------------------|
| <b>Gross weight</b>  | 0,255 kg                |
| <b>Net weight</b>    | 0,209 kg                |
| <b>Time Function</b> | 12sec-7min - adjustable |
| <b>Warranty</b>      | 2 Years                 |