

# OPTONICA




## LED Super Slim Interior Superficie Panel CCT

### Potencia


- 30W


### Color de luz



Cambio de color  
3000K-6000K

### Stamps





## Especificación técnica

|                                     |                             |
|-------------------------------------|-----------------------------|
| <b>Número de catálogo</b>           | 2587                        |
| <b>Brand</b>                        | Optonica                    |
| <b>Product Code</b>                 | DL30-A7                     |
| <b>Power</b>                        | 30W                         |
| <b>Energy Consumption</b>           | 30 kWh/1000h                |
| <b>Input voltage</b>                | AC175-265V                  |
| <b>Flux</b>                         | 3000 lm                     |
| <b>FLUX per watt</b>                | 100lm/W                     |
| <b>IP</b>                           | 20                          |
| <b>Dimmable</b>                     | No                          |
| <b>Correlated Color Temperature</b> | 3000K-6000K                 |
| <b>Light Color</b>                  | Cambio de color 3000K-6000K |
| <b>Wattage Equivalent</b>           | 200W                        |
| <b>EAN Code</b>                     | 3800156625877               |

|   |                  |
|---|------------------|
| <b>Energy Efficiency Label</b>                  | E                |
| <b>Beam angle</b>                               | 100°             |
| <b>Hole Size</b>                                | Φ65-310 mm       |
| <b>Power Factor</b>                             | 0.9              |
| <b>On/Off Cycles</b>                            | 25 000x          |
| <b>Instant On</b>                               | 0.1s             |
| <b>Material</b>                                 | ALU+PC           |
| <b>Operating Frequency</b>                      | 50-60 Hz         |
| <b>Temperature</b>                              | -20°C / +40°C    |
| <b>Ra ≥</b>                                     | 80               |
| <b>Life span</b>                                | 25 000 Hours     |
| <b>Color Code</b>                               | 830-860          |
| <b>Body Color</b>                               | White            |
| <b>Mount Type</b>                               | Recessed/Surface |
| <b>Lumen maintenance at end of service life</b> | 70%              |
| <b>Size of product</b>                          | φ330x19 mm       |
| <b>Size of package</b>                          | 340x340x35 mm    |
| <b>Items per pack</b>                           | 1                |

|                           |          |
|---------------------------|----------|
| <b>Items per box</b>      | 10       |
| <b>Color Of The Shell</b> | White    |
| <b>Color Change Mode</b>  | CCT      |
| <b>Gross weight</b>       | 0,960 kg |
| <b>Net weight</b>         | 0,812 kg |
| <b>Warranty</b>           | 2 Years  |