

OPTONICA



Mini panel cuadrado de superficie con retroiluminación LED

Potencia **Color de luz**

• 12W



Blanco cálido

Stamps





Especificación técnica

| | |
|-------------------------------------|---------------|
| Número de catálogo | 2992 |
| Brand | Optonica |
| Product Code | DL12-B1 |
| Power | 12W |
| Energy Consumption | 12 kWh/1000h |
| Input voltage | AC85-265V |
| Flux | 840 lm |
| FLUX per watt | 70lm/W |
| IP | 20 |
| Dimmable | No |
| Correlated Color Temperature | 2700K |
| Light Color | Blanco cálido |
| EAN Code | 3800156629929 |
| Energy Efficiency Label | G |

| | |
|---|-----------------|
| Beam angle | 120° |
| On/Off Cycles | 25 000x |
| Instant On | 0.1s |
| Operating Frequency | 50-60 Hz |
| Temperature | -20°C / +40°C |
| Ra ≥ | 80 |
| Life span | 25 000 Hours |
| Lumen maintenance at end of service life | 70% |
| Size of product | 160x160x28mm |
| Size of package | 17.5x3.5x17.5cm |
| Size of Box | 37.5x36x37cm |
| Items per pack | 1 |
| Items per box | 40 |
| Material | Aluminium |
| Gross weight | 0,217 kg |
| Net weight | 0,173 kg |
| Warranty | 2 Years |