

OPTONICA




Panneau LED Ultra Mince Encastré+Surface CCT

Puissance


- 30W


Couleur de lumiere



Changement de
couleur 3000K-
6000K

Stamps





Technical Specification

Reference catalogue	2587
Brand	Optonica
Product Code	DL30-A7
Power	30W
Energy Consumption	30 kWh/1000h
Input voltage	AC175-265V
Flux	3000 lm
FLUX per watt	100lm/W
IP	20
Dimmable	No
Correlated Color Temperature	3000K-6000K
Light Color	Changement de couleur 3000K-6000K
Wattage Equivalent	200W
EAN Code	3800156625877

Energy Efficiency Label	E
Beam angle	100°
Hole Size	Φ65-310 mm
Power Factor	0.9
On/Off Cycles	25 000x
Instant On	0.1s
Material	ALU+PC
Operating Frequency	50-60 Hz
Temperature	-20°C / +40°C
Ra ≥	80
Life span	25 000 Hours
Color Code	830-860
Body Color	White
Mount Type	Recessed/Surface
Lumen maintenance at end of service life	70%
Size of product	φ330x19 mm
Size of package	340x340x35 mm
Items per pack	1

Items per box	10
Color Of The Shell	White
Color Change Mode	CCT
Gross weight	0,960 kg
Net weight	0,812 kg
Warranty	3 Years