


# OPTONICA




## Downlight LED Mince CCT Changement de Couleur Dimmable

### Puissance

- 12W

### Couleur de lumiere



Changement de  
couleur 3000K-  
6000K

### Stamps





## Technical Specification

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Reference catalogue</b>          | 2583                              |
| <b>Brand</b>                        | Optonica                          |
| <b>Product Code</b>                 | DL16-A7                           |
| <b>Power</b>                        | 12W                               |
| <b>Energy Consumption</b>           | 12 kWh/1000h                      |
| <b>Input voltage</b>                | AC220-240V                        |
| <b>Flux</b>                         | 900 lm                            |
| <b>FLUX per watt</b>                | 75lm/W                            |
| <b>IP</b>                           | 44                                |
| <b>Dimmable</b>                     | Yes                               |
| <b>Correlated Color Temperature</b> | 3000K-6000K                       |
| <b>Light Color</b>                  | Changement de couleur 3000K-6000K |
| <b>Wattage Equivalent</b>           | 75W                               |
| <b>EAN Code</b>                     | 3800156625839                     |

|   |                |
|---|----------------|
| <b>Energy Efficiency Label</b>                  | F              |
| <b>Beam angle</b>                               | 100°           |
| <b>Hole Size</b>                                | φ155 mm        |
| <b>Power Factor</b>                             | 0.5            |
| <b>On/Off Cycles</b>                            | 25 000x        |
| <b>Instant On</b>                               | 0.2s           |
| <b>Material</b>                                 | Aluminium      |
| <b>Operating Frequency</b>                      | 50-60 Hz       |
| <b>Temperature</b>                              | -20°C / +40°C  |
| <b>Ra ≥</b>                                     | 80             |
| <b>Life span</b>                                | 25 000 Hours   |
| <b>Color Code</b>                               | 830-860        |
| <b>Lumen maintenance at end of service life</b> | 70%            |
| <b>Size of product</b>                          | φ170x32 mm     |
| <b>Size of package</b>                          | 175x170x45 mm  |
| <b>Size of Box</b>                              | 500x365x370 mm |
| <b>Items per pack</b>                           | 1              |
| <b>Items per box</b>                            | 40             |

|                     |          |
|---------------------|----------|
| <b>Gross weight</b> | 0,460 kg |
| <b>Net weight</b>   | 0,300 kg |
| <b>Warranty</b>     | 3 Years  |